



- Easily portable
- Second Control Control
  © Cold work no sparking
- Durable guide rails no moving parts
- Air cooling for mill cutter.
- Flexible mounting options

The Milling Machine has a light weight aluminium construction and it is equipped with high quality linear guideways and ball screws.

It is equipped with high quality air motors that power the machine reliably.

Machine can be delivered in different bed lengths and either with manual or pneumatic auto feed.


Normaco Lightweight Milling Machine is portable and pneumatically powered 2-axis milling machine.

It has been especially developed for applications where the extremely light weight of the machine is critical. For example for work in areas where the equipment must be carried by hand or rope access work.

The Portable Milling Machine is mounted directly to the work piece by bolting, welding or using a magnet base. It can also be secured with vacuum pads that allow the mounting to an non-ferrous material and without damaging the mounting area.

Pneumatic motor and low milling cutter speed make it possible to use the portable milling machine in areas where cold work is a requirement.





### **Mounting Options:**

### Standard:

Welded or bolted base

### Optional;

Magnet base 300kg

Vacuum clamping



www.normaco-tools.com



### Machine delivery includes

Milling machine with Spindle Motor

Transport and storage box

Analogue indicator for depth measurement

DIN standard lifting bolts (certified optional)

Set of hand tools

CE certification and operation manual





| Technical Data |  |  |
|----------------|--|--|
| Travel         | X-travel: *<br>425 mm /<br>1000 mm /<br>1500 mm              |  |
|                | Z-travel: 80 mm  |  |
| Feed           | X-axis: Manual /<br>Auto (optional)                          |  |
|                | Z-axis: Manual   |  |
| Spindle        | Motor:<br>Pneumatic 3kW /<br>Right angle 2.5kW<br>(optional) |  |
|                | Depth measurement with analogue read-out                     |  |
|                | Spindle BT30   |  |
|                | 850rpm   |  |
|                | Air Cooling  |  |

| X Axis Travel | Operational weight: | Shipping<br>weight: |
|---------------|---------------------|---------------------|
| 425mm         | 52 kg               | 90 kg               |
| 1000mm        | 65kg                | 120 kg              |
| 1500mm        | 77kg                | 150 kg              |


Spindle air motor must be used with Normaco Air safety device to maintain air motor warranty and CE— compliance.

All information contained in this document is subject to change without prior notice


<sup>\*</sup> length of continuous travel depends on mounting options.



#### Machine dimensions with manual feed



#### Machine dimensions with auto feed



www.normaco-tools.com